

EnviroRubber™

Recycled Rubber Flooring

EnviroRubber™ Recycled Rubber Flooring... Another Economical Flooring Solution!

New EnviroRubber™ Recycled Rubber Flooring is economical, versatile, and simple to use. EnviroRubber Flooring is designed to add color along with protection and durability to meet your flooring needs.

- Easy to install, economical, and versatile
- 48”x50’ Rolls in 4mm, 6mm and 9mm thickness
- Slip-resistant for increased safety
- Shock absorbing and sound reducing
- Environmentally friendly – manufactured with recycled materials
- Made in the USA
- Association of American Railways Approved
- ISO Approved
- Factory Sealed Finish is available

Wide variety of uses –

- events and trade shows
 - floor protection
 - transportation mats,
 - sports, health and fitness centers
 - golf resorts
 - weight rooms,
 - recreation areas
 - animal stalls and trailers
- and much more




TYPICAL SPECIFICATIONS

SHORE HARDNESS	ASTM D-2240	60 +/-5
DENSITY	ASTM D-792	65 lbs. cu. ft.
ELONGATION	ASTM D-412	60%
REBOUND	ASTM D-3574 (5/16")	45-60%
TENSILE	ASTM D-412	250 PSI
TABER ABRASION	ASTM C-501	0.45
FLAME SPREAD	ASTM E-84	135
SMOKE DEVELOPED	ASTM E-84	< 450
COMPRESSION SET	ASTM D-395B	12% or less
OZONE EXPOSURE	ASTM D-1149-86	No adversities
AGING RESISTANCE	ASTM D-750	No change
COEFFICIENT OF FRICTION	ASTM C1028-96	Dry = .83 - Wet = .98
ELECTRICAL RESISTANCE	ASTM F-150	
	(Surface to Ground)	1.9 x 105 Ohms
	(Surface to Surface)	4.4 x 105 Ohms
ELECTROSTATIC PROPENSITY	AATCC 134-1996	Neg. 0.4 KV


GRANULATE:	Color 1-3mm EPDM Black 8/16 SBR
BINDER:	Urethane
WARRANTY:	One Year by Manufacturer Materials. Liability is limited to replacement of product to original consumer. Urethane base recommended.
ADHESIVE:	Suitable for interior or exterior synthetic rubber.
LINE PAINT:	Rolls on end, minimum 55° Fahrenheit, less than 50% humidity.
STORAGE:	Should not vary more than 1/8" in ten ft. 30 days cure prior to installation of rubber. Under normal usage, light mopping, common detergents, if needed.
SUB-FLOORING:	
NEW CONCRETE/ASPHALT:	
MAINTENANCE:	

Manufactured with recycled materials.







#601



#603




#604




#606




#607




#608




#609




#611



#613



#614




#615




#622




#623




#625



#626




#627



#629



#632



#638



#652

PLEASE NOTE: Actual colors of finished product may vary slightly.